



total access control

1803 AUTO DIALER TELEPHONE ENTRY SYSTEM



features

- Provides visitor access control into apartment buildings, gated communities, condominiums, office buildings, factories and industrial sites
- Visitors use the 1803 to communicate with a resident, who can then grant or deny them access from their touch-tone telephone
- Provides service for up to 1000 residents
- Programmable directory codes can be set from 1 to 4 digits
- Surface or flush mount styles available



total access control

THE MODEL 1803 is an ideal telephone entry system that is suited for applications that do not require a directory, or in applications where a separate directory exists. Visitors are easily identified by voice communication and can be granted or denied access directly from a touch-tone telephone.

TECH SPECS

electrical requirements
16 VAC, 20 VA System power (250 ma)
U.L. listed power transformers provided
Ringer equivalence: 0.0A Jack Type: RJ11C or W

communication
Full duplex Hands free
Optional handset available (ADA compliant)

operating temp
10°F to 145°F
-12°C to 62°C
Optional heater kit available for colder climates

capacity
125, 500 or 1000 phone numbers, 10 area codes
4 digit entry codes same as system memory
5 digit entry codes = 6

door/gate control
Two relays allow for control of both a vehicular gate and a pedestrian gate

advanced features
Programmable directory codes can be set from 1 to 4 digits in length
10 & 11 digit dialing capability
LCD Programming display
Built in clock/calendar:
Entry code time zones
Four hold-open time zones
Flash entry codes
DTMF tone output allows for use with KSU, PBX and systems with an auto-attendant

programming methods
System keypad
Touch tone telephone

display & mounting styles
Surface or flush mount
Display for programming assistance and shows 'open' when access is granted


listing
FCC (US) DUF6VT-12874-OT-0
DOC (CAN) 1736 4507 A
Complies with UL 294 ETL Listed

dimensions
Surface mount: Height: 13 inches
Width: 11 1/4 inches Depth: 4 3/4 inches @ top
3 3/4 inches @ bot
Flush mount unit: Height: 13 1/2 inches
Width: 12 inches Depth: 2 1/2 inches
Flush mount kit: Height: 14 1/2 inches
Width: 12 3/4 inches Depth: 3 7/8 inches
Shipping Weight: Approximately 15-20 lbs
Warranty: 2 year limited factory warranty



Telephone Entry System

DoorKing's auto-dialer series provide convenient access control for apartment buildings, gated communities, condominiums, office buildings and industrial sites. These systems provide voice communication for visitors and can control two separate doors or gates.



circuit board
Advanced microprocessor controlled circuit board



telephone access
systems use a modular design concept that makes installation and service easy



2 mounts
Surface and flush are available



surge suppressors
help to protect circuit boards from transient voltage spikes



dtmf tone output
allows these systems to be used with PBX, KSU and telephone systems with auto-attendants



Built-in display
indicates door/gate has been opened



built-in time clock
provides automatic relay activation for "hold open" periods

