



total access control

1808 AUTO DIALER

TELEPHONE ENTRY SYSTEM



features

- Provides visitor access control in residential or commercial applications
- Visitors use the 1808 to communicate with a resident, who can then grant or deny them access from their touch-tone phone
- Provides service for up to 1000 residents
- Programmable directory codes can be set from 1 to 4 digits
- Ideal for residential, multi-home applications

1808



total access control

TECH SPECS

electrical requirements

16 VAC, 20 VA System power (250 ma)
U.L. listed power transformer provided
Ringer equivalence: 0.0A Jack Type: RJ11C or W

communication

Full duplex
Hands free

operating temp

10°F to 145°F
-12°C to 62°C
Optional heater kit available for colder climates

capacity

125, 500 or 1000 phone numbers,
10 area codes
4 digit entry codes same as system memory
5 digit entry codes = 6

door/gate control

Two relays allow for control of both a vehicular gate and a pedestrian gate

advanced features

Programmable directory codes can be set from 1 to 4 digits in length
10 & 11 digit dialing capability
Built in clock/calendar
Entry code time zones
Four hold-open time zones
Flash entry codes
DTMF tone output allows for use with KSU, PBX and systems with an auto-attendant

programming methods

System keypad
Touch tone telephone

mounting styles

Surface mount with lighted key pad

listing

FCC (US) DUF6VT-12874-OT-0
DOC (CAN) 1736 4507 A
Complies with UL 294 ETL Listed

dimensions


Height: 7 3/8 inches Width: 11 inches
Depth: 6 3/8 inches @ top
4 3/4 inches @ bottom
Shipping Weight: Approximately 15-20 lbs
Warranty: 2 year limited factory warranty

THE MODEL 1808 is an ideal telephone entry system that is suited for applications that have limited space and can be used in residential as well as commercial applications. Visitors are easily identified by voice communication and can be granted or denied access directly from a touch-tone telephone. With the small built in directory option, this system is ideal for small, multi resident applications.



Intercom

Voice communication provided by the 1808 allows homeowners to speak with their guest for positive ID before granting access.



circuit board

advanced microprocessor controlled circuit board



telephone access

systems use a modular design concept that makes installation and service easy



lighted keypad and display



surge suppressors

help to protect circuit boards from transient voltage spikes



built-in time clock

provides automatic relay activation for "hold open" periods



dtmf tone output

allows these systems to be used with PBX, KSU and telephone systems with auto-attendants



flash entry codes

allow entry on a single day only, then automatically deactivate themselves

